

BLANK PAGE



IS 3568: 1990

भारतीय मानक

गोल अग्र भाग वाले प्लास — विशिष्ट

(पहला पुनरीक्षण)

Indian Standard **ROUND NOSE PLIERS — SPECIFICATION** (First Revision)

UDC 621.881.4

@ BIS 1991

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG **NEW DELHI 110002**

FOREWORD

This Indian Standard was adopted by the Bureau of Indian Standards on 5 June 1990, after the draft finalized by the Assembly Hand Tools Sectional Committee had been approved by the Production Engineering Division Council.

These types of pliers are generally used for holding and gripping of items in situations where it is inconvenient or impossible to use hands These pliers are made in many styles. General types, which are used in abundance have been covered in this standard.

This standard was first issued in 1966. This revision has been taken up in order to align the specification with the work done at the international level as well as to give the references of revised latest standards.

Load test and torsion tests have also been modified. The hardness values have been aligned with that of other pliers.

Nominal sizes 150, 175 and 200 are quite popular and being used in the country. Though these sizes have not been covered in ISO standard (ISO covers 140, 160 and 180 mm pliers), but based on their demand, these have been included in this standard.

While formulating this standard, considerable assistance has also been taken from ISO 5745: 1982 Pliers and nippers — Pliers for gripping and manipulating — Dimensions, issued by the International Organization for Standardization (ISO).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2: 1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

ROUND NOSE PLIERS — SPECIFICATION

(First Revision)

1 SCOPE

1.1 This standard covers the dimensions and other requirements for the round nose pliers.

2 REFERENCES

2.1 The following Indian Standards are necessary adjuncts to this standard:

IS No.

Title

2615: 1989

Technical supply conditions for pliers, pincers and nippers (second

11526:1986

Nomenclature for pliers, pincers

and nippers

3 TYPES

Type A - Round, short nose pliers; and

Type B — Round, long nose pliers.

4 NOMENCLATURE


4.1 For the purpose of this standard, the nomenclature as given in IS 11526: 1986 shall apply.


5 DIMENSIONS

5.1 The dimensions of the both types of round nose pliers (short as well as long) shall be as given in Tables 1 and 2 respectively.

Table 1 Dimensions for Round, Short Nose Pliers

All dimensions in millimetres.







Nominal Size	L	Tolerance on L	D ₁ Max	L ₃	Tolerance on L ₃	T Max	₩₃ Max
100	100	± 6	1.0	16	0 -3	6	14
125	125	±6	1.2	20	0 ~ 5	8	16
150	150	±7	2.0	25	0 6	10	18
175	175	±8	2.5	3 0	0 -6	10	20
20 0	200	±8	3.2	37	+0 -8	12	22

Table 2 Dimensions for Round, Long Nose Pliers

All dimensions in millimetres.





Nominal Size	L	Tolerance on L	D ₁ Max	L ₃	Tolerance on L ₃	T Max	W ₃ Max
100	100	±6	1.5	28	0 -3	6	12
125	125	±6	2.0	36	0 -5	6	14
150	150	±7	2.2	38	0 -6	11	16
160	160	±7	2.5	42	0 -6	11	16
(180)	180	±8	3.0	05	+0 -8	12	18

NOTE - Size shown in paranthesis () is non-preferred.

6 HARDNESS

6.1 The hardness of jaw shall be in the range of 350 to 510 HV (\approx 35 to 50 HRC).

7 GENERAL REQUIREMENTS

7.1 The material, manufacture, workmanship and finish, tests, preservation and packing and sampling shall conform to IS 2615: 1989.

8 TEST

In addition to tests specified in IS 2615: 1989, the following tests shall also be carried out.

8.1 Bend Test

The pliers, when tested by bending 1.25 mm diameter hard-drawn steel wire, shall work satisfactorily and shall not show any sign of damage or distortion or indentation on the noses of the plier on completion of the test.

8.2 Torsion Test

The round nose pliers shall be tested for this requirement as per 9.4 of 1S 2615: 1989. The test torque to be employed shall be as indicated in Table 3.

8.3 Handle Load Test

The round nose pliers shall be tested for permanent set as given in 9.5 of IS 2615:1989. The load to be employed shall be as given in Table 3 and the permanent set shall not exceed the values given in Table 3.

9 DESIGNATION

9.1 The round nose pliers shall be designated by its commonly used name, nominal size and number of this standard.

Example:

10 MARKING


A round nose plier of nominal size 150 mm shall be designated as:

10.1 The pliers shall be clearly and legibly stamped with the nominal size indication of the source of manufacture. The year of manufacture may also be legibly marked if required by the purchaser.

Round Short Nose Plier — IS 3568 — 150

Table 3 Test Requirements for Round Nose Pliers

(Clauses 8.2 and 8.3)



Nominal Torsion Test		Load Test		
Size L	Torque	Twist a°	Bending Moment (FxL ₁)*	Permanent Set
mm	Nm	Max	Nm	mm
100	0.80	20°	22.5	1
125	1.35	20°	39.4	1
150	2.15	20°	50	1
160	2.35	20°	52	1
175	2•75	20°	60	1
(180)	2.9	20°	63	1
200	3.2	20°	75	1

NOTE — Nominal size shown in paranthesis () is non-preferred.

^{*}For load application, see 9.5 of IS 2615: 1989.

 $[\]dagger S = W_1 - W_2$ (see IS 2615 : 1989).

Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. PE 05 (4827)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
		· · · · · · · · · · · · · · · · · · ·

BUREAU OF INDIAN STANDARDS

Headquarters:

BOMBAY 400093

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002	Telegrams: Manaksansth
Telephones: 331 01 31, 331 13 75	(Common to all Offices

Regional Offices:	Telephone
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	$\left\{\begin{array}{c} 331 \ 01 \ 31 \\ 331 \ 13 \ 75 \end{array}\right.$
Eastern: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola GALGUTTA 700054	87 86 62

Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	53 38 43
Southern: C. I. T. Campus, IV Cross Road, MADRAS 600113	41 29 16
Western: Manakalaya, E9 MIDC, Marol, Andheri (East)	6 32 92 95

Branches: AHMADABAD.	BANGALORE.	BHOPAL.	BHUBANESWAR.
COIMBATORE.	FARIDABAD.	GHAZIABAD.	GUWAHATI.
HYDERABAD. J	AIPUR. KANPUR.	PATNA. THIRU	VANATHAPURAM.